

Synthetic

HANABI Lube ATF DX-III

Premium Performance
Automatic Transmission Fluid



OVERVIEW

HANABI Lube ATF DX-III is a superior automatic transmission fluid developed for passenger vehicles equipped with automatic transmissions, offering enhanced performance over conventional ATF products. It is also well-suited for automatic transmissions featuring a lock-up clutch. The fluid delivers exceptional quality through its outstanding oxidation stability, excellent low-temperature fluidity, optimal tribological performance, and superior shear stability.

PRODUCT APPLICATIONS

- Suitable for use in all transmission systems of passenger cars, trucks, buses, and construction machinery where an ALLISON C-4 type fluid is specified
- Compatible with hydraulic systems requiring a GM DEXRON III type fluid

PERFORMANCE LEVEL

- GM : DEXRON®-II, IID, IIE, DEXRON®-III, IIIH, TASA
- Ford : MERCON®, WSS M2C 138CJ, 166H, WSS M2C 922A1, 924A, FNR5
- Honda : ATF Ultra II, ATF-Z1(except in CVTs)
- Hyundai / Kia : SP-II, SP-III, SP-IV, SP-IV M, JWS 3314/9683, Red 1
- JASO : M315-2013 1A, M315-2013 2A • Allison : C-3 & C-4
- Mitsubishi : Diaqueen SP-II, SP-III, SP-IV, Diaqueen AW, Diaqueen J2
- Nissan : Matic Fluid C, D, J, K
- Suzuki : ATF, ATF HP, ATF 2326, ATF 2384K, JWS 3309, ATF 3314, ATF 3317
- Toyota : ATF D-II, D-III, ATF T-III, T-IV • Volvo : CE 97340
- VW : SHP (19FL, 24A), G 055 025 A2(JWS 3309), TL 521 62
- ZF : TE-ML 09, 11A, 11B

CUSTOMER BENEFITS

Excellent Viscosity Performance

The very high viscosity index coupled with excellent viscosity stability during operation ensures no viscosity changes and thus prolongs the service life of the device.

Great Combination of Components

Oxidation stability and cleaning performance of base oils and additives prevent corrosion, rust, and sludge formation. High-quality base oils provide high foam stability, excellent low-temperature fluidity, good start operation in cold weather and high oxidation stability. The advanced friction modifiers provide more stable friction property.

REMARKS

Kinematic Viscosity, mm ² /s @ 40°C	35.1
Kinematic Viscosity, mm ² /s @ 100°C	7.48
Viscosity Index	228
Pour Point °C	-49
Flash Point °C	188
Package (Liters)	1T, 4T, 20, 200