



Fully Synthetic

HANABI Lube DX C3

Premium diesel engine oil
for Ultimate performance

OVERVIEW

HANABI Lube DX C3 is an engine oil formulated with advanced VHVI base oil and Low SAPS additive technology, developed in accordance with ACEA C category engine oil specifications. It is well-suited for passenger cars, SUVs, and RVs alike. Its proprietary additive technology minimizes sulfated ash content, effectively extending DPF service life while enhancing DPF performance — all without compromising engine durability.

PRODUCT APPLICATIONS

- Passenger cars with gasoline and diesel engine
- Designed for passenger vehicles equipped with DOHC, Turbo-charger, CRDI, and catalytic converter systems
- Suitable for diesel vehicles featuring exhaust after-treatment devices, including EGR and DPF systems

PERFORMANCE LEVEL

ACEA C3-16, API SN/CF, MB 229.51/229.52, BMW Long Life-04, VW 502.00/505.00/505.01

CUSTOMER BENEFITS

Protection of After Treatment System

Advanced low SAPS additive technology extends the lifespan of the exhaust gas after-treatment system by preventing clogging of DPF.

Anti-Wear Property

Excellent wear protection maximizes the life time of engine and all its components.

Superior Low Temperature Performance

Using high quality Group III Base oil, it provides excellent low-temperature properties as producing quick and easy start-ups in cold weather.

Clean Technology

Outstanding detergent and dispersant additives provide prominent resistance for varnish at high temperature and for sludge deposit at low temperature.

REMARKS

SAE Grade	5W-30	5W-40
Kinematic Viscosity, mm ² /s @ 40°C	68.0	79.2
Kinematic Viscosity, mm ² /s @ 100°C	11.9	13.6
Viscosity Index	172	176
Pour Point °C	-36	-39
Flash Point °C	236	246
Package (Liters)	1T, 4T, 200	1T, 4T, 200